



SUPER-TACK® SYNTHETIC ROOFING UNDERLAYMENT INSTALLATION INSTRUCTIONS

DECK

Roof decks should be structurally sound and meet or exceed minimum requirements of the roof deck manufacturer and local building codes.

STACK underlayment is designed for use under asphalt shingles and metal roofing and must be covered within 180 days of application. Always follow safe roofing practices and OSHA safety requirements. Always wear and use fall protection devices when working on roofs. Use caution when walking or standing on STACK underlayment in wet or dusty conditions that may reduce traction. Failure to use proper safety equipment and footwear can result in serious injury.

FASTENERS

If the roof will not be covered with asphalt shingles or metal roofing on the same day, STACK underlayment must be attached to the roof deck using plastic or steel cap fasteners having a minimum 1" diameter cap.

For installations covered by asphalt shingles or metal roofing on the same day of install, roofing nails and pneumatic nail guns may be used for all slopes. Staples may be used for installations on slopes 2:12 and above.

All fasteners should be driven straight and flush with the surface. Consult local building codes for fastener type and spacing requirements.

LAP REQUIREMENTS - ALL SLOPES

If two or more pieces are required to continue a course, lap the ends at least 4" (must be at least 12" for slopes 2:12 to less than 4:12).

End laps in a succeeding course should be located at least 6" from laps in the preceding course. Lap STACK a minimum of 6" from both sides over all hips, ridges and valleys. Where the roof meets a wall, extend a minimum 4" up the wall.

SLOPES 4:12 OR GREATER

Always lay STACK parallel to the eaves, lapping each course at least 2" over the underlying course unless in high wind applications which will need to be 4".

If STACK will not be covered on the same day with asphalt shingles (extended exposure up to 180 days), use only plastic or steel cap fasteners having a minimum 1" diameter cap for all slopes. Fasten in both the overlapping area and the field area of STACK underlayment.

Additional fasteners may be required in high wind regions per local building codes.

SLOPES 2:12 TO LESS THAN 4:12

On all lower slope applications, cover the deck with two layers of STACK.

Roofing nails, pneumatic nail guns and staples may be used for same day installations. If STACK will not be covered on the same day (extended exposure up to 180 days), use only plastic or steel cap fasteners having a minimum 1" diameter cap.

Additional fasteners may be required in high wind regions per local building codes.

Caution:

Roof surface may be slippery, especially when dusty, wet or icy. Use a fall protection system when installing. Wear soft-soled shoes. Walk with care.

Falling Hazard:

Secure area below work and materials on roof. Unsecured materials may slide when placed on roof. Place on level plane or secure to prevent sliding. Wear a hard hat.

Caution:

Safety glasses should always be worn when using power tools. Wear gloves when installing to avoid cuts and abrasions.



Manufactured in North America
by Atlantic Coated Papers
www.super-tack.com
www.atlanticcoatedpapers.com
info@acp99.com