

# TRUE GRIT™ 15

## ROOFING UNDERLAYMENT

Proudly made in North America



Florida Building Code Approved FL22409  
Meets ASTM D226 Type II and ASTM D4869

**TRUE GRIT™ 15** is the best value 15# synthetic roofing underlayment on the market today. It features **TRUE GRIT Technology™**, a top-side coating that provides an incredibly coarse, sandpaper like grip. It provides superior traction underfoot and allows you and your team to focus on installing, while **TRUE GRIT Technology™** focuses on your safety.

### Benefits

- **TRUE GRIT Technology™**
- No tears - Much stronger than 15# asphalt felt
- Light - Easier to handle and carry than felt
  - 10 Sq. TRUE GRIT 15 weighs 18 lb
  - 4 Sq. 15# asphalt felt weighs 42 lb
- **30 Day UV exposure**
- No asphalt - will not rot, dry-out, nor support mold growth
- No buckling, warping or cracking
- Dependable long term moisture protection for the roof
- Lays flat for quick and easy install
- Less laps - 48" wide TRUE GRIT 15 vs. 36" asphalt felt
- Cool grey color to reduce heat absorption on install
- **20 Year limited warranty**
- 100% Recyclable - Considered a green building product

### Specifications

ROLL SIZE	10 SQUARES	4 SQUARES
Surface Covered	1000 ft <sup>2</sup> (92.9 m <sup>2</sup> )	400 ft <sup>2</sup> (37.2 m <sup>2</sup> )
Length	250 ft (76.2 m)	100 ft (30.5 m)
Width	48" (1219 mm)	48" (1219 mm)
Rolls per Pallet	56	120
Weight per Roll	18 lbs	8 lbs

PROPERTIES	TEST METHOD	TRUE GRIT™ 15
Breaking Strength (lbf/in-width)	ASTM D 226	61 Longitudinal (with fiber grain)
	ASTM D 226	61 Transverse (across fiber grain)
Tear Resistance; min; (lbf)	ASTM D 4073	69 MD Longitudinal (with fiber grain)
	ASTM D 4073	63 CMD Transverse (across fiber grain)
Pliability	ASTM D 228	Pass - Longitudinal / Transverse
Behavior (loss) on Heating	ASTM D 228	- 0.0
Liquid Water Transmission [Pass/Fail]	ASTM D 4869	Pass
Dimensional Stability (%)	ASTM D 1204	2.5 Longitudinal (with fiber grain)
	ASTM D 1204	2.5 Transverse (across fiber grain)
Unrolling @ 30°F and 140°F; [Pass/Fail]	N/A	Pass
Nominal Thickness	ASTM D1777	5.5 mils



Atlantic Coated Papers 1605 McEwen Dr. Whitby, Ontario L1N 7L4 1-886-299-1675

[atlanticcoatedpapers.com](http://atlanticcoatedpapers.com)